

Asheville Daily Citizen.

BEGIN TO-DAY.
CAPTURE THAT ELEGANT PIN.
SEE SECOND PAGE.

YOUR CHANCE.
SEE THE GOLD WATCH OFFER
ON SECOND PAGE.

VOLUME VII.—NO. 44

ASHEVILLE, N. C., FRIDAY EVENING, JUNE 26, 1891.

PRICE 5 CENTS.

WHERE THE SWAMPS NEST.

For a cool place in summer, for health and recreation, visit Linville, Grandfather Mountain, and the beautiful region surrounding them.

Regular sales of real estate at Linville on and after June 1st 1891. Business lots and residence sites sold at private sale only.

The Escala Inn was opened the 1st of June, under the management of Mr. James T. Skiles. Regular daily stage from Cranberry.

LINVILLE

INVESTIGATION AS TO

Climate,
Water Supply,
Drainage,
Drives,
Parks,
Scenery,
Plans,
Building Sites,
Investments.
LINVILLE IMPROVEMENT CO.
Linville, N. C.

ANALYSIS OF WATER

USED AT THE

ASHEVILLE SODA WATER FACTORY.

217 HAYWOOD ST.

CERTIFICATE OF ANALYSIS.
STATE ANALYST'S OFFICE, 207 Franklin St.
BOSTON, MASS., April 21, 1901.

To Chas. H. Campbell, Asheville, North Carolina.

The sample of water submitted for analysis has been carefully examined with the following results:

The water taken in quart per 100,000:
Solids, volatile..... 2.00
Total..... 2.40
Grains per gallon..... 2.40
This water is almost entirely free from organic matter, shows no very slight traces of iron sulphate and lime. The water is very excellent in all respects. It is very seldom we find water so free from organic or mineral matter.

H. L. BOWKER,
State Analyst.

CORTLAND BROS.,

Real Estate Brokers,
And Investment Agents.

NOTARY PUBLIC.

Loans securely placed at 8 per cent.
Office:
24 & 26 Patton Avenue Second floor
604111.

REAL ESTATE.

WALTER R. OWEN, W. W. Wray.

GWYN & WEST,

(Successors to Walter B. Gwyn)

ESTABLISHED 1881

REFER TO BANK OF ASHEVILLE.

REAL ESTATE.

Loans Securely Placed at 8 Per Cent.

Notary Public. Commissioners of Deeds

FIRE INSURANCE.

OFFICE: Southeast Court Square.

J. W. SCHARTLE,

MERCHANT TAILOR

NO. 42 NORTH MAIN ST.

Just received, a full line of English and do Western notions for sewing and summer.

62-24-104

WILLS BROS.,

ARCHITECTS.

28 Patton Avenue.

Next to M. C. A. building, P. O. Box 506.

8071 d3m

FOR RENT OR SALE.

Either home owned by T. Wilson Sharp-
lest, corner French Broad Avenue and Hay-
wood Street. These houses are located near
the center of town, commanding good views,
high elevations. For information apply to
JOHN CHILDS.

WHOLESALE AND RETAIL

A FULL LINE OF

COLGATE'S TOILET AND LAUNDRY

SOAPS.



THE TURKISH BATH AND PALM

Are two of the best 5 cent toilet soaps on the market. Colgate's White Clematis, 10 cents, three for 25. Other kinds as low as 40 cents per dozen. Colgate's Octagon leads all the laundry soaps. It will wash the finest fabrics without injury.

A. D. COOPER,

PROVIDER OF GROCERIES, PROVISIONS, ETC.,
Court Square, Corner Main and College Sts.

WE HAVE JUST RECEIVED

—AN—

EXTRAORDINARY BARGAIN

IN HEMSTITCHED 45 INCH

EMBROIDERED FLOUNCES

GOODS THAT RETAILED FOR

\$1.50 TO \$2.25 PER YARD.

WE CAN OFFER THE ENTIRE LINE AT

75 CENTS.

White, Black, Pink, Blue and various colors

White, White on Black.

"BON MARCHÉ."

37 N. Main Street.

STARTLING FACTS.

When the adulteration of Food Products becomes so general that it is necessary in larger cities to organize associations for the protection of manufacturers and dealers, it is high time the consumer consider well the importance of dealing with reliable houses.

POWELL & SNIDER

Have met with unusual success in their endeavor to establish and maintain a high standard of

Wholesomeness and Purity

In the QUALITY of the goods they sell.

Our large and ever increasing trade is, we think, evidence sufficient to convince all "Doubting Thomases" that we are selling goods at a very low and reasonable rate.

Respectfully,

Powell & Snider,

Wholesale and Retail Grocers.

HOW TO MAKE MONEY.

The way to make money is to save it. And the way to save it is to have your prescriptions filled at Carmichael's drug store, and you will find by doing so you will save from 25 to 30 per cent. on every prescription. We do not take goods that the people know the price and then charge two prices for a prescription to make up the loss. You know clerk hire and house rent must be paid and the profits must be averaged some way. A hint to the wise is sufficient. A full line of De-Vault Flavoring Extracts in stock. Mr. J. Taylor Amis and Mr. Chas. W. De-Vault are with me and will be pleased to meet their friends and customers. Don't forget the place. Carmichael's drug store, No. 20 South Main street, Asheville, N. C.

THE MATTLAND SCHOOL,

HOME AND DAY SCHOOL FOR GIRLS.

No. 40 French Broad Avenue.

MRS. BURWYN MATTLAND, PRINCIPAL.

Complete teachers and thorough instruction. Lessons in Music, Chinese Painting at Kensington Embroidery are continued during the summer vacation.

THE REVOLVING DISC

FLY FANS

ARE THE WONDER OF THE AGE.

Nickle plated and very nicely finished; handsomest on the market; are superior to all others; an ornament to the table; a luxury to the household; a blessing to the sick; a pleasure to the industrious; and a necessity to all, where flies are troublesome. The rapidly revolving discs not only frighten and drive away the flies, but cause a pleasant circulation of air, thereby adding to the enjoyment of every meal during the summer months. No home is complete without one. Special price is offered on above described fans until July 1st. Sold only by

THAD W. THRASH & CO.,

41 Patton Ave.

CHINA, GLASS, FURNITURE, HOUSE-FURNISHINGS, ETC.

When awards are made the contractor will be required to give bond to indemnify the city of Asheville against all claims for damages of any kind or nature whatsoever, and for the faithful performance of his contract.

In submitting proposals the sealed envelope must be so endorsed as to indicate, before being opened, the particular work for which the bid is made; it should then be enclosed in another envelope and addressed to the mayor at his office.

Reasonable grounds for supposing that any bidder is interested in more than one bid for the same item will cause the rejection of all bids in which he is interested.

Proposals should be addressed to the mayor of Asheville, N. C., and endorsed, "Proposals for grading, curbing and paving."

Bidders must present satisfactory evidence of their ability to do the work, and that they have been fully prepared with the necessary capital to begin and complete the work to be contracted for.

None Paving.

The stone blocks to be of hard, durable granite, free from bulges, lumps or cavities, evenly squared and of uniform quality. No 1 blocks each measuring on the face or upper surface not less than eight (8) nor more than twelve (12) inches in length, and not less than three (3) nor more than four and a half (4 1/2) inches in width, and in depth not less than six (6) nor more than seven (7) inches; the dimensions at base to vary not more than half an inch from the corresponding dimensions at the top, the stones to have, when set, full joints for at least half their depth on the sides and ends, the top to show an even, uniform surface, and in all respects like the specimen blocks at the engineer's office.

All paving and other stones necessary to be removed shall be taken up and removed immediately from the line of the work. The sub-soil or other matter is to be then to be excavated and removed to the depth of twelve (12) inches below the top line of the proposed new pavements, and then to be compacted with a roller. The sub-soil or other matter is to be without respect to the character of the sub-soil or rock as it now exists.

The stone blocks are to be laid at right angles with the line of the street, stretching from curb to curb, with such a cross as the engineer may direct; each course of blocks to be of uniform width and depth, and so laid that all longitudinal joints shall be broken by a lap of at least one inch, and all transverse joints not more than three-eighths of an inch in width. When thus laid, the pavement shall be immediately covered with clean creek gravel in proper quantities, and covered thereon with a layer of sand, to be left with a coating of clean, sharp bar sand.

No charge shall be made by the contractor for hindrance or delay from any cause during the progress of any portion of the work embraced in these specifications. The contractor shall not assign, underlet or make a sub-contract for the execution of any portion of the work, or the delivery of materials, without the sanction, in writing, of the engineer.

The contractor shall be held liable to guard the public thoroughly from liability to accident during the progress of the work, both by day and night, and will be held responsible for any damages the city may have to pay in consequence of his neglecting the necessary precautions. The contractor will be required to keep in repair for twelve (12) months after its completion, the whole of the work, except in cases where the repairs may be rendered necessary by causes clearly beyond his control.

Any bidder who shall fail, after a week's notice being given of the acceptance of his bid, to furnish the required security, shall forfeit his bid to the city.

Bidders will send to the engineer's office specimen paving blocks, curb stones and samples of sand and gravel.

Vitrified Brick Paving.

Lay one course of vitrified paving brick on edge on cushion of sand, made even and of the shape and form required for the pavement when completed; such bricks to be laid in straight lines stretching from curb to curb (the brick being assorted for that purpose, if necessary), closely and evenly, edgewise of the brick and crosswise of the street, and at right angles with the curb line thereof (except at intersection of other streets or avenues, where said brick shall be laid on an angle of forty-five degrees, or as said engineer may direct), with the joints broken not less than two inches; but no pieces shall be used, except to break joints, and then not less than half a brick.

Sufficient dry, medium fine, clean sand shall be swept into the joints or crevices between said brick, thus laid, to fill them out half full.

Said brick shall then be tamped by using a 2x8 straight edge, tamping back and forth on said sand, with a wooden or iron tamper of sufficient weight (not less than 50 pounds), until the unevenness is taken out.

Finally, spread over such pavement about three-fourths of an inch of clean sand and leave it to be driven into said joints and crevices by travel.

The quality of brick shall be as follows: They shall be strong, regular in size and shape; free from flaws, cracks, seams or breaks, made expressly for paving and burned to vitrification, and able to endure the tests hereinafter specified; but hard burned brick, made expressly for paving and of the above description, except as to vitrification, may be accepted, if they will endure said tests.

The brick shall endure the following tests: The modulus of rupture for transverse strength shall not be less than 1,600 pounds to the square inch. The brick must not absorb more than two percent. of their own weight of water; shall not contain more than one percent. of water of imbibition or injury; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to disintegrate or injure; and shall have the power to resist abrasion equal, at least, to the best Richmond, Va., granite or like grade of granite, when tested as follows: A layer of sound, hard, broken stone four inches in depth, properly sized, shall be compacted by rolling, with small chills of iron, in such a manner as to